

### Product Information

The Euroflex Blockout is a frontlit 240gsm single-sided banner media made of a hybrid mix of PES and PVC with a PET grey backing. Available in gloss

It provides a high-quality, uniform print surface with excellent low glare finish, plus guarantees great light-blocking properties.

It is compatible with most ink technologies currently available.

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

### Technical Data

Material	PES/PVC Hybrid
Backing	PET Blockout Grey
Finishes	Gloss
Thickness	240gsm
Temperature durability	-20 up to +70°C
Ink compatibility	UV, Eco, Solvent and Latex

### Standard Dimensions

1600mm (wide) x 50m (long)  
1370mm (wide) x 50m (long)

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.