

**ET7-107 1.5W SMD3030 1LED IP65/DC12V**
**CE ROHS IP65**

**ET7-107 : 1.5W**

1. Adopt TOP 3030SMD LED no light spots, with a low lumen recession and good consistency.
2. 3030 LED SMD With a low power consumption and high lumen value, 125lm/LED, a long lifespan maintenance-free.
3. With a plastic injection technique for outer cover, this unique structure grants a better cooling effect.
4. IP Rate: IP66-IP67, waterproof.
5. DC 12V low voltage input, reliable and safe.
6. Adopt series-parallel connection circuit, 20/40pcs per string, if 40pcs connect together must be on the each end of string connect DC12V , each module could be singled out.

**Application**

This product is applicable for 10-20cm glowing character, advertisement board, round light box or local lighting.

| Photometric Characteristics         |                                       |
|-------------------------------------|---------------------------------------|
| Model                               | ET7-107                               |
| Led Type                            | 3030 SMD HIGH POWER LED               |
| LED Brand                           | Chip from Epistar                     |
| Viewing Angle                       | 20*60°                                |
| LED Qty                             | 1LED                                  |
| Lifespan                            | 50,000H                               |
| Working Voltage                     | DC12V                                 |
| Consumption                         | ≤1.5W                                 |
| Driving Method                      | CV                                    |
| Stand Length in Serial Connection   | 20pcs                                 |
| Maximum Length in Serial Connection | ≤40pcs                                |
| Shell                               | White ABS inject/Good Quality Plastic |
| Dimension                           | 49mm*31.5mm*H14mm                     |
| Available Color                     | W/WW/CW                               |
| Certification                       | CE & ROHS                             |
| Working Temperature                 | -40°C ~ +60°C                         |
| Store Temperature                   | -50°C ~ +70°C                         |
| IP Degree                           | IP66-67x                              |

**MTX3030-h1.5w**
**CE ROHS**