


3W SMD3030 3LED IP65/DC12V
CE ROHS IP65

ET7-108 : 3W

1. Uses TOP 3030 SMD LED no hot spot, with a low lumen recession and good consistency.
2. 3030 LED SMD With a low power consumption and high lumen value, 240lm/LED, a long lifespan maintenance-free.
3. With a plastic injection technique for outer cover, this unique structure grants a better cooling effect.
4. IP Rate: IP65, waterproof.
5. DC 12V low voltage input, reliable and safe.
6. Adopt series-parallel connection circuit, 20pcs per string, if 20pcs connect together must be on the each end of string connect DC12V , each module could be singled out.

Application

This product is applicable for 10-20cm glowing character, advertisement board, round light box or local lighting.

Photometric Characteristics	
Model	ET7-108 SMD LED Inject Module
Led Type	3030 SMD HIGH POWER LED
LED Brand	Chip from Epistar
Viewing Angle	15*60°
Luminous Flux (Lm)	≥240lm
LED Qty	3LED
Lifespan	50,000H
Working Voltage	DC12V
Consumption	≤3W
Driving Method	CV
Stand Length in Serial Connection	20pcs
Maximum Length in Serial Connection	≤20pcs
Shell	White ABS inject/Good Quality Plastic
Dimension	72mm*22mm*H10mm
Available Color	W/WW/CW
Certification	CE & ROHS
Working Temperature	-40°C ~ +60°C
Store Temperature	-50°C ~ +70°C
IP Degree	IP65

MTX3030-h3w
CE ROHS