



A EUROTECH GROUP BRAND

TOPTAPE

Item no. EV-AT

Product Information

Application tape based on a special impregnated paper with low tensile elongation and high wet strength.

Suitable for transferring self/adhesive letters produced from cast and calendered PVC colored films according to CAD/CAM techniques.

Especially to be emphasised are the following properties:

- The natural rubber adhesive guarantees an excellent adhesion on PVC films because of the relatively high coating weight.
- The impregnated carrier paper shows an excellent stability of shape, with no curl even under moist conditions.
- Based on the tape translucence, the alignment - even of small letterings and logos, is simplified.
- The Application Tape can be rewound easily from the roll.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Technical Data

Carrier	Special paper, impregnated
Adhesive	Natural rubber
Adhesion	2,40N/cm (+/- 10%)
Thickness	0,10mm (+/- 5%)

Standard Dimensions

153mm (wide) x 91m (long)
305mm (wide) x 91m (long)
610mm (wide) x 91m (long)
1220mm (wide) x 91m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.