

### Product Information

Monomeric PVC Film (white gloss, 80  $\mu$ ) with clear solvent based acrylic adhesive (permanent), laminated with a one-sided clay-coated silicone paper (135 g/m<sup>2</sup>) and equipped with a clear dispersion acrylic adhesive (permanent).

Suitable for bonding various surfaces for example on commercial slabs, glass, metal or plastic. Especially suitable for the use on smooth as well as slightly curved surfaces.

It is ideal for short term presentation of advertising panels.

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

### Technical Data

Carrier	Monomeric PVC film, highly stabilized, calendered
Thickness	80 $\mu$ (ISO 4593)
Adhesive	Clear acrylic dispersion, permanent
Adhesion	5,5 N/cm
Liner	One-sided clay-coated silicone paper (135 g/m <sup>2</sup> )
Tensile Strength md:	> 20 MPa (DIN EN ISO 527)
Tensile Strength cd:	> 20 MPa (DIN EN ISO 527)
Elongation md:	> 160% (DIN EN ISO 527)
Elongation cd:	> 180% (DIN EN ISO 527)
Application temperature	+10 up to +40°C
Temperature durability	-40 up to +80°C
Outdoor durability	3 years (unprinted film)

### Standard Dimensions

1370mm (wide) x 50m (long)  
1550mm (wide) x 50m (long)