

# GLOSS LONG TERM HIGH-TACK

Item no. EV-P-GHT

### **Product Information**

Polymeric PVC Film (white gloss,  $75~\mu$ ) with clear solvent based acrylic adhesive (permanent), laminated on a two-sided PE-coated silicone paper (144 g/m²).

The PVC offers high dimensional stability.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

For hard-to-stick substrates, resistent to low-energy surfaces such as polyethylene, polypropylene, polycarbonate, acrylonitrile butadiene styrene. For long term applications.

## **Shelf Life**

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

## **Recommendations for Laminating**

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

## **Technical Data**

Carrier Polymeric PVC, highly stabilized,

calendered

Thickness 75 µ (+/- 5%)

Adhesive Clear solvent-based acrylic, perma-

nent

Adhesion

11,3 N/cm

Liner

Two-sided PE coated silicone paper

 $(144 \text{ g/m}^2)$ 

Application temperature

+10 up to +40°C

Temperature durability

-40 up to +80°C

Outdoor durability

5-7 years (unprinted film)

#### Standard Dimensions

1370mm (wide) x 50m (long) 1520mm (wide) x 50m (long)

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with teh regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After us, dispose of the waste product in accordance with local/national authorities.