



# BANNER UPS® BY BUDNICK BAN013

Clear Banner Ups Mini Adhesive Grommet PowerTabs

Banner Ups Crystal Clear Mini PowerTabs® consists of a lamination of high strength engineered polymer film with a high performance, high tack acrylic pressure-sensitive adhesive. The tab is die cut to a unique shape designed to maximize tensile strength of the tab and the banner media to which it is attached. For the most demanding exterior conditions PowerTabs® may be used in conjunction with Banner Ups PowerTape® to create a banner of maximum strength. Crystal Clear Mini Banner Ups PowerTabs® have a smaller profile than the original PowerTabs by eliminating the neck loop for a more streamline look.

Backing/Carrier	Co-Extruded Polymer Tape	Tensile		Min. Application Temp	40° F
Adhesive	Acrylic	Elongation		Min. Service Temp	
Thickness	15 Mils	Adhesive Activation	Pressure	Max Short-Term Temp	150° F
		Adhesion (unwind)	110 oz/in	Max Long-Term Temp	

### PRODUCT FEATURES

- No sewing, grommeting, or special tools required
- Use Banner Ups PowerTabs® adhesive grommet tabs to turn your digital image into a super-strong outdoor banner – instantly
- Use PowerTabs® adhesive grommet tabs with virtually any banner media, Tyvek®, Coroplast®, Foamcore®, scrim vinyl, or paper
- For outdoor banners over 8 feet, add PowerTape® for ultimate strength
- Triangular shape for corners only
- Small, clear, no neck loop
- Good for indoor or outdoor use.
- Tab Size: 3? x 1.5?

### MARKETS SERVED

- Signage, Banners, & Printing

### ADHESIVE TAPE APPLICATIONS

- Banner hanger
- Fastener for fabric or film

### ADHESIVE TAPE COLORS

- Clear

Data provided by Budnick Converting, Inc.

The physical properties listed are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must carry out their own tests to determine the suitability of the product for their internal use. Information is given in good faith, but without warranty.

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil.

Shelf life from date of manufacture is based on the product being stored at 70°F(21°C) / 50% relative humidity out of direct sunlight.

Specification compliance is dynamic and should only be used as a general guide. Always confirm that the tape you are interested in currently complies with all specification requirements. Please verify that the product number that you select is available in the proper size and color to meet your specification.