

Product Information

Soft PET film (transparent gloss, 40 μ) with solvent-based acrylic adhesive (permanent), laminated on a single-sided PE-coated silicone paper (100 g/m²).

This laminate has been design by Eurotech to specifically protect wide format digital print against vandalism and specifically the use of inks and paints like graffiti and markers. Because of this it is also usable as a whiteboard or dry erase film.

It is a perfect laminate solution for flat and minimally curved surfaces in interior and exterior situations, such as facias, building signage, whiteboards and window graphics.

Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Technical Data

Carrier	Soft PET, highly stabilized, calendared
Thickness	40 μ (+/- 5%)
Adhesive	Solvent-based acrylic, permanent
Adhesion	7,5 N/cm
Liner	Single-sided PE coated silicone paper (100 g/m ²)
Application temperature	+10 up to +40°C
Temperature durability	-30 up to +80°C
Outdoor durability	5 years (unprinted film)

Standard Dimensions

1370mm (wide) x 50m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with teh regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After us, dispose of the waste product in accordance with local/national authorities.