

Product Information

The Flatlite is a fast-drying, wide-format laminated banner media product that represents a premium option for those in need of durable and top-quality banner material suitable for both indoor and outdoor use.

Its extensive range of benefits, including print quality and outdoor durability, makes it an excellent choice for a variety of graphic design and advertising projects

No need for lamination.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Technical Data

Outer layers	PVC Matt finish
Inner layer	PET Greyback
Thickness	420gsm
Application temperature	+10 up to +40°C
Temperature durability	-20 up to +70°C
Ink compatibility	UV, Eco-solvent and Solvent

Standard Dimensions

914mm (wide) x 45m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.