



# BANNER UPS® BY BUDNICK TTAPEDC2

## TigerTape2 Economy Double Sided Banner Hem Tape

Banner Ups TigerTape® 2 is a 4.5 mil economy grade double coated polyester (PET) carrier film coated on both sides with a high deposition of a high tack acrylic pressure-sensitive adhesive (PSA). A high-performance banner hem tape specifically designed for the most demanding bonding applications, TigerTape® 2 provides a permanent bond on foams, plastics, metals, and composite materials subjected to a broad range of environmental conditions.

TigerTape® 2 is highly UV, temperature, and plasticizer resistant making it ideal for banner hemming applications. Materials should be stored at 70°F (21°C) with 50% relative humidity.

<b>Backing/Carrier</b>	PET - Polyester	<b>Tensile</b>		<b>Min. Application Temp</b>	50° F
<b>Adhesive</b>	Acrylic	<b>Elongation</b>		<b>Min. Service Temp</b>	-40° F
<b>Thickness</b>	4.5 Mils	<b>Adhesion (liner)</b>	130 oz/in	<b>Max Short-Term Temp</b>	
		<b>Adhesion (unwind)</b>	130 oz/in	<b>Max Long-Term Temp</b>	275° F

### PRODUCT FEATURES

- High conformability
- Economic pricing
- Great outdoor performance
- Plasticizer resistant
- High tack & peel
- Excellent anchorage to foam

### MARKETS SERVED

- Signage, Banners, & Printing

### ADHESIVE TAPE APPLICATIONS

- Banner hemming applications
- Trophy industry
- General purpose bonding
- Coated paint surfaces

Data provided by Budnick Converting, Inc.

The physical properties listed are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must carry out their own tests to determine the suitability of the product for their internal use. Information is given in good faith, but without warranty.

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil.

Shelf life from date of manufacture is based on the product being stored at 70°F(21°C) / 50% relative humidity out of direct sunlight.

Specification compliance is dynamic and should only be used as a general guide. Always confirm that the tape you are interested in currently complies with all specification requirements. Please verify that the product number that you select is available in the proper size and color to meet your specification.

