



A EUROTECH GROUP BRAND

## GLOSS LAMINATE

Item no. EV-ECO-GL



PVC FREE

### Product Information

This Laminate is a high-gloss, super clear film made of polypropylene. It has a thickness of 60 microns and is designed for both indoor and outdoor use.

The film and adhesive include UV stabilizers for added protection. The adhesive is a pressure-sensitive permanent clear, high-coat weight adhesive, ensuring a strong bond.

It is also **PVC-free**, making it environmentally friendly. It is suitable for flat surfaces and can be used for laminating over UV inks and difficult surfaces.

### Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

### Technical Data

Carrier	High-gloss Clear PP film
Thickness	60 $\mu$ (+/- 5%)
Adhesive	High-coat clear acrylic, permanent
Adhesion	17N/25mm
Liner	Single-sided PE kraft paper (120 $\mu$ m)
Application temperature	+10 up to +40°C
Temperature durability	-30 up to +80°C
Outdoor durability	5 years

### Standard Dimensions

1370mm (wide) x 50m (long)

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After us, dispose of the waste product in accordance with local/national authorities.

**Eurotech Australia**  
72 John Street  
Welshpool 6106 WA

☎ 1800 30 61 61  
✉ [info@eurotech.com.au](mailto:info@eurotech.com.au)  
🌐 [eurotech.com.au](http://eurotech.com.au)

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every sage a test should be conducted on the original material.