



A EUROTECH GROUP BRAND

ECOFLAT

Item no. EV-ECO-RU300



PVC FREE

Product Information

The Ecoflat is a white matt PP film designed specifically for retractable banner displays.

This **PVC-free** film measures 300 microns in thickness and boasts a super flat high-quality print surface.

It features a light-blocking backing in grey and is compatible with both Latex and UV printers.

The film also offers excellent dimensional stability, making it ideal for over-lamination if needed.

The Ecoflat is perfectly suited for retractable banners.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Technical Data

Outer layers	Matt White PP Film
Inner layer	PET Grey
Thickness	300 micron
Ink compatibility	UV and Latex

Standard Dimensions

914mm (wide) x 50m (long)
1370mm (wide) x 50m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

Eurotech Australia
72 John Street
Welshpool 6106 WA

☎ 1800 30 61 61
✉ info@eurotech.com.au
🌐 eurotech.com.au

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every sage a test should be conducted on the original material.