

### Product Information

The Evolve Print and Cut PVC Film is a calendared polymeric white gloss vinyl composed of PVC, engineered specifically for print and cut applications.

This film boasts an outdoor durability of 7 years, making it ideal for various outdoor uses.

The product's clear permanent adhesive ensures effortless weeding of vinyl cut lettering and easy application.

Its high-quality polymeric composition ensures exceptional performance and limited shrinkage even in harsh conditions.

It has been designed for all print and cut applications, like labels.

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

### Technical Data

Carrier	Polymeric soft PVC, highly stabilized, calendared
Thickness	90 μ (+/- 5%)
Adhesive	Clear solvent-based acrylic, permanent
Adhesion	15N/25mm
Liner	Two-sided PE coated silicone paper (80 g/m <sup>2</sup> )
Application temperature	+10 up to +40°C
Temperature durability	-40 up to +80°C
Outdoor durability	7 years (unprinted film)

### Standard Dimensions

1370mm (wide) x 50m (long)

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.