

VIVIDItem no. EV-BL200

Product Information

The Vivid is a translucent PET film specially designed for lightboxes and illuminated displays, coated with a matt finish, that not only reduces glare but also enhances image density, delivering exceptional print quality.

Vivid printouts are characterised by their high ink density, vivid and eye-catching colors, and outstanding image resolution, whether in the presence or absence of light.

Installation is a breeze thanks to the excellent rigidity and flatness of the base polyester film.

Technical Data

Material PET

Coating Resin

Thickness 275gsm

Application temperature +10 up to +40°C

Temperature durability -20 up to +70°C

Ink compatibility Eco, Solvent, UV and Latex

Shelf Life

1 year when stored in the original packaging between 10°C and 30°C at 65% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Standard Dimensions

1270mm (wide) x 30m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with teh regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After us, dispose of the waste product in accordance with local/national authorities.